

Za Stodolou 144, 251 01 Modletice

Přírubové ložisko LMT

MODEL NO.	NUMBER OF BALL ROWS	MAIN DIMENSIONS											BASIC LOAD RATING						
		INSCRIBED CIRCLE	OUTER DIAMETER	LENGTH	FLANGE	HOLE FOR ATTACHMENT	SQUA-RENESS	ECCEN-TIRICITY(MAX.)	c(k gf) Co(kgf)										
		dr	TOLE-RANCE D	TOLE-RANCE L	TOLE-RANCE D1	W	H	A	F	d1	d2	h							
LMT6	4	6	12	-0	19		28	18	5	20	3.5	6	3.1			21	27		
LMT8	4	8	-0	15	-0.013	24	0	32	21	5	24	3.5	6	3.1			27	41	
LMT10	4	10	-0.009	19	-0	29	-0.20	40	25	6	29	4.5	7.5	4.1	0.012	0.012	38	56	
LMT12	4	12		21		30		42	27	6	32	4.5	7.5	4.1			42	61	
LMT13	4	13		23	-0.016	32		43	29	6	33	4.5	7.5	4.1			52	79	
LMT16	5	16		28		37		48	34	6	31	22	4.5	7.5	4.1			79	120
LMT20	5	20	-0	32	-0	42		54	38	8	36	24	5.5	9	5.1			88	140
LMT25	6	25	-0	40	-0	59	0	62	46	8	40	32	5.5	9	5.1			100	160
LMT30	6	30	-0.01	45	-0.019	64	-0.30	74	51	10	49	35	6.6	11	6.1	0.015	0.015	160	280



LMT6-LMT13



LMT16-LMT40

