

Za Stodolou 144, 251 01 Modletice

Přírubové ložisko LMF

MODEL NO.	NUMBER OF BALL ROWS	MAIN DIMENSIONS												BASIC LOAD RATING				
		INSCRIBED CIRCLE		OUTER DIAMETER		LENGTH		FLANGE			HOLE FOR ATTACHMENT			SQUARENESS	ECCEN-TRICITY(MAX.)	c(kgf)	Co(kgf)	
		d _r	TOLERANCE	D	TOLER	L	TOLERANCE	D1	K	H	Φ	d1	d2					h
LMF6	4	6		12	-0	19		28	22	5	20	3.5	6	3.1			21	27
LMF8S	4	8		15		17		32	25	5	24	3.5	6	3.1			18	22
LMF8	4	8	-0	15	-0.011	24	0	32	25	5	24	3.5	6	3.1			28	40
LMF10	4	10	-0.009	19	-0	29	-0.20	40	30	6	29	4.5	7.5	4.1	0.012	0.012	38	56
LMF12	4	12		21		30		42	32	6	32	4.5	7.5	4.1			52	80
LMF13	4	13		23		32		43	34	6	33	4.5	7.5	4.1			52	80
LMF16	5	16		28	-0.013	37		48	37	6	38	4.5	7.5	4.1			79	120
LMF20	5	20	-0	32	-0	42		54	42	8	43	5.5	9	5.1			90	140
LMF25	6	25		40		59		62	50	8	51	5.5	9	5.1			100	160
LMF30	6	30	-0.010	45	-0.016	64		74	58	10	60	6.6	11	6.1	0.015	0.015	160	280
LMF35	6	35	-	52	-0	70	0	82	64	10	67	6.6	11	6.1			170	320
LMF40	6	40		60		80		96	75	13	78	9	14	8.1			220	410
LMF50	6	50	0-0.012	80	-0.019	100	-0.30	116	92	13	98	9	14	8.1	0.020	0.020	390	810
			-0		-0													
LMF60	6	60	-0.015	90	-0.022	110		134	106	18	112	11	17.5	10.8	0.025	0.025	480	1020

